

CLAIMS

1. A display device comprising:  
a display part; and  
a base part supporting the display part,  
5 said base part comprising:  
a tilt unit to mount the display part  
thereon for rotation about a first axis;  
a first member directly or indirectly  
supporting the tilt unit;  
10 a second member disposed in a facing  
relationship with the first member;  
a guide part provided on one of the first  
member and the second member for guiding the first member  
and the second member for relative rotation therebetween  
15 about a second axis different from the first axis; and  
at least one low friction member disposed  
between the first member and the second member.
2. The display device according to claim 1,  
further comprising a cover having an aperture, wherein  
20 the tilt unit is fixed to the first member through the  
aperture of the cover, and the first member is disposed  
between the cover and the second member.
3. The display device according to claim 1,  
further comprising a cover, wherein the tilt unit is  
25 fixed to the cover, the cover being directly or  
indirectly fixed to the first member, the first member  
being disposed between the cover and the second member.
4. The display device according to claim 1,  
wherein said at least one low friction member comprises a  
30 plurality of low friction members, the plurality of low  
friction members being held on one of the first member  
and the second member and slidable with respect to the  
other of the first member and the second member.
5. The display device according to claim 3,  
35 wherein the low friction member comprises one of a ball-  
shaped member and a mushroom-shaped member.

104050 5634600

Sul  
A1

Sul  
A2